

Product Specifications

Style Number	VV457
Construction	Waterproof Foamed Core
Edge Profile	Enhanced Painted Bevel
Nominal Dimensions	9" wide, 72" long

	US Units	Metric Units
Actual Product Width	8.98"	23 cm
Actual Product Length	72.05"	183 cm
Wear Layer Thickness	30 mil (0.03")	0.76 mm
Overall Product Thickness	0.472"	12 mm
Core Thickness	0.354"	9 mm
Attached Underlayment	Attached Cork	
Attached Underlayment Thickness	0.118"	3 mm
Finish	UV Acrylic	
Installation Methods	Floating or Direct Glue	
Profile	Angle/Tap	
Country of Origin	Imported	

Packaging

Area per Box	26.95 sq ft	2.5 sq m
Pieces per Box	6 pcs	
Weight per Box	68.14 lbs	30.9 kg
Boxes per Pallet	28 boxes	



1029 Cloud Pine

Colors



COREtec Originals Premium VV457



Performance

Static Load (ASTM F970)	Passes
Residual Indentation (ASTM F1914)	Passes
Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Radiant Panel (ASTM E648)	Passes, Class I
Slip Resistance (ASTM D2047)	ADA compliant

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

USF Lifetime

[Residential Resilient Limited Warranty - Defects, Wear, Waterproof, Petproof](#)

USF 10 Year Medium Commercial

Certifications


GreenGuard Gold Certified

Coordinating Trim



Baby Threshold*


06V26 | 94"



T-Molding*


06V31 | 94"

06W31 | 94"




Quarter Round

06V27 | 94"



Overlap Stairnose*

06V29 | 94"



Flush Stairnose

06V30 | 94"

*Packaged with molding track



COREtec Originals Premium VV457

Stair Tread



Stair Tread
03Z70 | 48"