

Product Specifications

Style Number	VV024	
Construction	Waterproof Foamed Core	
Edge Profile	Micro Bevel	
Nominal Dimensions	7" wide, 48" long	
	US Units	Metric Units
Actual Product Width	7.13"	18 cm
Actual Product Length	48.03"	122 cm
Wear Layer Thickness	20 mil (0.02")	0.5 mm
Overall Product Thickness	0.314"	8 mm
Core Thickness	0.256"	6.5 mm
Attached Underlayment	Attached Cork	
Attached Underlayment Thickness	0.059"	1.5 mm
Finish	UV Acrylic	
Installation Methods	Floating or Direct Glue	
Profile	Angle/Tap	
Country of Origin	Imported	

Packaging

Area per Box	38.03 sq ft	3.53 sq m
Pieces per Box	16 pcs	
Weight per Box	63.05 lbs	28.59 kg
Boxes per Pallet	35 boxes	



210 Kingswood Oak

Colors

				
210 Kingswood Oak	211 Nantucket Oak	703 Waterfront Oak	704 Saginaw Oak	705 Ivory Coast Oak
Color Variation: V2 - Slight	Color Variation: V2 - Slight	Color Variation: V3 - Moderate	Color Variation: V2 - Slight	Color Variation: V3 - Moderate
				
706 Alabaster Oak	707 Blackstone Oak	708 Hudson Valley O	714 Marsh Oak	715 Fidalgo Oak
Color Variation: V4 - Substantial	Color Variation: V4 - Substantial	Color Variation: V4 - Substantial	Color Variation: V2 - Slight	Color Variation: V2 - Slight

COREtec Originals Classics VV024



Performance

Static Load (ASTM F970)	Passes
Residual Indentation (ASTM F1914)	Passes
Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Radiant Panel (ASTM E648)	Passes, Class I
Slip Resistance (ASTM D2047)	ADA compliant

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

- USF Lifetime
- [Residential Resilient Limited Warranty - Defects, Wear, Waterproof, Petproof](#)
- 10 Year Light Commercial
- Com Ub Bond 4100/4151







Certifications

- FloorScore Certified
- GreenGuard (Certification, Gold, Private Label) Certified



COREtec Originals Classics VV024

Coordinating Trim

Baby Threshold*
 BT7CT | 94"
 01V02 | 94"
 01V06 | 94"

T-Molding*
 TM7CT | 94"
 02V24 | 94"
 02V28 | 94"

Quarter Round
 QTRCT | 94"
 01V27 | 94"
 01V31 | 94"


Overlap Stairnose*
 01V76 | 94"
 01V80 | 94"

Flush Stairnose
 FS7HU | 94"
 02V01 | 94"
 02V06 | 94"

Overlap Reducer
 01V52 | 94"
 01V56 | 94"

*Packaged with molding track

Coordinating Metal Trim

Finish
 Satin Silver

T-Mold
 USC17


Satin Nickel
Stair Cap

USC24

Installation Range

Profile Size	Installation Range
3.5mm	1.5mm to 3.5mm heights
5.5mm	3.6mm to 5.5mm heights
8mm	6mm to 8mm heights

Stair Tread



Stair Tread
 03Z70 | 48"