

Product Specifications

Style Number	VV012
Construction	Waterproof Foamed Core
Edge Profile	Enhanced Painted Bevel
Nominal Dimensions	7" wide, 48" long

	US Units	Metric Units
Actual Product Width	7.09"	18 cm
Actual Product Length	48.03"	122 cm
Wear Layer Thickness	20 mil (0.02")	0.5 mm
Overall Product Thickness	0.314"	8 mm
Core Thickness	0.256"	6.5 mm
Attached Underlayment	Attached Cork	
Attached Underlayment Thickness	0.059"	1.5 mm
Finish	UV Acrylic	
Installation Methods	Floating or Direct Glue	
Profile	Angle/Tap	
Country of Origin	Imported	


Packaging

Area per Box	23.64 sq ft	2.19 sq m
Pieces per Box	10 pcs	
Weight per Box	39.68 lbs	17.99 kg
Boxes per Pallet	35 boxes	




756 Nares Oak


Colors



756 Nares Oak




757 Marianas Oak



760 Manila Oak



761 Calypso Oak



762 Mornington Oak




765 Aden Oak




771 Aurora Oak



772 Pasadena Oak



4036 Bay Oak



5033 Jerome Oak

Color Variation: V2 - Slight

Color Variation: V2 - Slight

COREtec Originals Enhanced VV012



8006 Miles Oak
Color Variation: V2 - Slight

Performance

Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Radiant Panel (ASTM E648)	Passes, Class I
Slip Resistance (ASTM D2047)	ADA compliant

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

- USF Lifetime
- Residential Resilient Limited Warranty - Defects, Wear, Waterproof, Petproof
- USF 10 Year Medium Commercial


Certifications

GreenGuard Gold Certified


Coordinating Trim




Baby Threshold*
01V19 | 94"
01V20 | 94"




T-Molding*
02V62 | 94"



Quarter Round
01V46 | 94"



Overlap Stairnose*
01V95 | 94"



Flush Stairnose
02V17 | 94"

*Packaged with molding track

Stair Tread



Stair Tread
03Z70 | 48"

