

**Product Specifications**

<b>Style Number</b>	VV870	
<b>Construction</b>	Solid Polymer Core	
<b>Edge Profile</b>	Enhanced Painted Bevel	
<b>Nominal Dimensions</b>	12" wide, 24" long	
	<b>US Units</b>	<b>Metric Units</b>
<b>Actual Product Width</b>	12.01"	31 cm
<b>Actual Product Length</b>	24.02"	61 cm
<b>Wear Layer Thickness</b>	20 mil (0.02")	0.5 mm
<b>Overall Product Thickness</b>	0.196"	5 mm
<b>Core Thickness</b>	0.157"	4 mm
<b>Attached Underlayment</b>	Attached Cork	
<b>Attached Underlayment Thickness</b>	0.039"	1 mm
<b>Installation Methods</b>	Floating or Direct Glue	
<b>Profile</b>	ANGLE TAP	
<b>Country of Origin</b>	Imported	

**Packaging**

<b>Area per Box</b>	28.03 sq ft	2.6 sq m
<b>Pieces per Box</b>	14 pcs	
<b>Weight per Box</b>	47.4 lbs	21.5 kg
<b>Boxes per Pallet</b>	42 boxes	



12251 Serena Limestone

**Colors**



Color Variation: V3 - Moderate

**Performance**

<b>Static Load (ASTM F970)</b>	Passes
<b>Residual Indentation (ASTM F1914)</b>	Passes
<b>Resistance to Heat (ASTM F1514)</b>	Passes
<b>Resistance to Light (ASTM F1515)</b>	Passes
<b>Resistance to Chemicals (ASTM F925)</b>	Passes
<b>Radiant Panel (ASTM E648)</b>	Passes, Class I
<b>Slip Resistance (ASTM D2047)</b>	ADA compliant

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

# CT PPLUS E TILE

## Warranties

30 Years

Residential Resilient Limited Warranty - Defects, Wear, Waterproof, Petproof


7 Year Light Commercial

## Coordinating Trim




**Baby Threshold\***

BT3HU | 94"




**T-Molding\***

TM3CT | 94"



**Quarter Round**

QTRCT | 94"



**Flush Stairnose**

FS4CT | 94"

\*Packaged with molding track

## Coordinating Metal Trim



**Reducer**

USC29

USC30



**T-Mold**

USC32

USC33



**Stair Cap**

USC26

USC27

**Finish**

Satin Silver

Satin Nickel

## Installation Range

Profile Size	Installation Range
3.5mm	1.5mm to 3.5mm heights
5.5mm	3.6mm to 5.5mm heights
8mm	6mm to 8mm heights