

Product Specifications

| | | |
|--|-------------------------|---------------------|
| Style Number | VV704 | |
| Construction | Waterproof Foamed Core | |
| Edge Profile | Pressed Bevel | |
| Nominal Dimensions | 7" wide, 48" long | |
| | US Units | Metric Units |
| Actual Product Width | 7.05" | 18 cm |
| Actual Product Length | 48.03" | 122 cm |
| Wear Layer Thickness | 20 mil (0.02") | 0.5 mm |
| Overall Product Thickness | 0.295" | 7.5 mm |
| Core Thickness | 0.197" | 5 mm |
| Attached Underlayment | Attached Cork | |
| Attached Underlayment Thickness | 0.039" | 1 mm |
| Finish | UV Acrylic | |
| Installation Methods | Floating or Direct Glue | |
| Profile | Angle/Tap | |
| Country of Origin | Imported | |

Packaging

| | | |
|-------------------------|------------|-----------|
| Area per Box | 18.8 sq ft | 1.74 sq m |
| Pieces per Box | 8 pcs | |
| Weight per Box | 30.6 lbs | 13.87 kg |
| Boxes per Pallet | 70 boxes | |



3016 Blended Umber

Colors



Warranties

Residential Resilient Limited Warranty - Defects, Wear, Waterproof, Petproof


USF 10 Year Medium Commercial

COREtec Originals Premium VV704


Coordinating Trim




Baby Threshold*
BT7CT | 94"



T-Molding*
TM7CT | 94"



Quarter Round
QTRCT | 94"



Flush Stairnose
FS7HU | 94"

*Packaged with molding track

Coordinating Metal Trim



Reducer
USC20
USC21



T-Mold
USC23
USC24



Stair Cap
USC17
USC18

Finish

Satin Silver

Satin Nickel

Installation Range

| Profile Size | Installation Range |
|--------------|------------------------|
| 3.5mm | 1.5mm to 3.5mm heights |
| 5.5mm | 3.6mm to 5.5mm heights |
| 8mm | 6mm to 8mm heights |

Stair Tread



White Riser
USC02 | 48"



Stair Tread
03Z70 | 48"