

Product Specifications

Style Number	CRT02	
Construction	Waterproof Foamed Core	
Edge Profile	ENHANCED PAINTED BEVEL	
Nominal Dimensions	12" wide, 24" long	
	US Units	Metric Units
Actual Product Width	12"	30.48 cm
Actual Product Length	24"	60.96 cm
Wear Layer Thickness	22 mil (0.022")	0.55 mm
Overall Product Thickness	0.403"	10.25 mm
Core Thickness	0.256"	6.5 mm
Attached Underlayment	Attached Soft Step	
Attached Underlayment Thickness	0.148"	3.75 mm
Finish	UV Acrylic	
Installation Methods	Floating or Direct Glue	
Profile	Lock N Place Clips	
Country of Origin	Imported	


Packaging

Area per Box	28.03 ft²	2.6041 m²
Pieces per Box	14 pcs	
Weight per Box	55.25 lbs	25.06 kg
Boxes per Pallet	36 boxes	



1039 Morning Fog Terrazzo

Colors




1039 Morning Fog
Terrazzo




2118 Warm Biscotti
Concrete




2119 Soft Umber Concrete




5116 Silvermist Concrete




5117 Mineral Gray Slate



9015 Eclipse Slate



9016 Nightfall Slate



9017 Cosmic Noir Marble

Balanced Retreat

Performance

Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Smoke Density (ASTM E662)	Passes
Radiant Panel (ASTM E648)	Passes, Class I


Warranties

- USF Lifetime
- USF 10 Year Medium Commercial


Coordinating Trim




Baby Threshold*
BT7CT | 94"



T-Molding*
TM7CT | 94"



Quarter Round
QTRCT | 94"



Flush Stairnose
FS9HU | 94"

*Packaged with molding track

Stair Tread



Stair Tread
TR2CT | 48"